

Single-Unit 2 through 24 fibers

HITACHI Inspire the Next

Product Highlights

- REACH & RoHS 2 compliant.
- Made in USA.
- 900 micron buffered design recommended for easy termination.
- All multimode, and singlemode cables (except OM1) utilize bend-insensitive optical fibers.
- Each fiber is color coded for easy identification.
- Ideal intra-building cable solution.
- Flexible and easy to handle.
- Lightweight, flexible aramid yarns enhance strength.

Options

- OS2 optical fibers with enhanced bend-insensitive performance are available.
- Standard jacket colors are:
 Yellow: OS2
 Orange: OM1 & OM2
 Aqua: OM3 & OM4
Note: Violet for OM4 is available
- OM4 optical fibers with extended 10 gigabit Ethernet distances are available.
- Wideband multimode fiber is available.

Applications

- Applications include 10, 40 & 100 gigabit Ethernet, Fibre Channel, Video, Security, Automation.

Standards

- TIA/EIA-568-C.3
- ISO/IEC 11801, 2nd edition
- Telcordia GR-409-CORE

Single-Unit (Riser) (UL) OFNR c(UL) OFNR FT4

PART NUMBERS BY FIBER COUNT

FIBERS	62.5 UM OM1	50 UM OM2	50 UM OM3	50 UM OM4	50 UM OM5	8.3 UM OS2
2	60514-2	60063-2	60463-2	61842-2	62724-2	60012-2
4	60515-4	60516-4	60520-4	61865-4	62741-4	60014-4
6	60515-6	60516-6	60520-6	61865-6	62741-6	60014-6
8	60515-8	60516-8	60520-8	61865-8	62741-8	60014-8
10	60515-10	60516-10	60520-10	61865-10	62741-10	60014-10
12	60515-12	60516-12	60520-12	61865-12	62741-12	60014-12
24	60515-24	60516-24	60520-24	61865-24	62741-24	60014-24

SPECIFICATIONS BY FIBER COUNT

FIBERS	CABLE O.D.		RECOMMENDED MAXIMUM LOADS				CABLE WEIGHT	
			INSTALL		OPERATION			
	in.	mm	lbs-f	N	lbs-f	N	lbs/1000 ft	kg/1000m
2	.190	4.8	128	569	38	171	11.5	17.1
4	.190	4.8	128	569	38	171	13.0	19.4
6	.190	4.8	128	569	38	171	14.5	21.6
8	.230	5.8	160	712	48	214	18.5	27.6
10	.230	5.8	160	712	48	214	20.0	29.8
12	.230	5.8	160	712	48	214	21.5	32.0
24	.330	8.4	288	1282	86	385	50.3	74.9

Cable Characteristics

Note: Part number rows in upper table directly correspond to cable characteristic rows in the same location of the lower table.

Single-Unit

Multimode and Singlemode

Single-Unit (Riser) (UL) OFNR c(UL) OFNR FT4

Optical Specifications

TIA/EIA-568-C.3 | ISO/IEC 11801, 2nd edition | Telcordia GR-409-CORE

Fiber type	Max. Attenuation (dB/km)		Min OFL Bandwidth (MHz-km)		Min EMBc Bandwidth (MHz-km)		Gb Ethernet distance (m)		10 Gb Ethernet distance (m)	
	850nm (MM)	1300nm (MM)	850nm (MM)	1300nm (MM)	850nm (MM)	1300nm (MM)	850nm (MM)	1300nm (MM)	850nm (MM)	1300nm (MM)
OM1	3.5	1.0	200	500	220	N/A	300	550	33	N/A
OM2	3.0	1.0	700	500	950	N/A	750	550	150	N/A
OM3	3.0	1.0	1500	500	2000	N/A	1000	550	300	N/A
OM4	3.0	1.0	3500	500	4700	N/A	1100	550	550	N/A
OM5*	3.0	1.0	3500	500	4700	N/A	1100	550	550	N/A
	1310nm (SM)	1550nm (SM)	1310nm (SM)	1550nm (SM)	1310nm (SM)	1550nm (SM)	1310nm (SM)	1550nm (SM)	1310nm (SM)	1550nm (SM)
OS2	0.5	0.5	N/A	N/A	N/A	N/A	> 25,000	> 40,000	10,000 - 25,000	40,000

Hitachi Cable America reserves the right to revise any specifications.

*OM5 optical fiber tested by glass manufacturer and exceeds the requirements of all applicable industry standards.

Mechanical Specifications

- Bend radius, no load = 10x cable overall diameter
- Bend radius, load = 15x cable overall diameter


plus
CORNING
ClearCurve® Optical Fiber

FIBER

Cable Temperature Ranges

Storage: -40° to 70°C (-40° to 158°F)
 Installation: -10° to 60°C (14° to 140°F)
 Operating: -20° to 70°C (-4° to 158°F)

Features



DIELECTRIC MATERIALS

RISER

Overall Jacket

Flame-retardant thermoplastic




Diagram scale approx. 2:1

