

Hookup Wire

UL Style: 1571/10064/1061
 UL Voltage Rating: 30V/30V/300V
 UL Temp: 80°C/105°C/80°C



PVC, Irradiated Cross-Linked PVC, and ETFE insulations available.
Various colors and gauges available upon request.
UL approved.
Suitable for JST connectors.
APPLICATIONS Internal wiring of electronic equipment.
Eco-Index: RoHS Values
<1000ppm <100ppm <1000ppm <1000ppm <1000ppm
Pb Cd Cr+6 Hg PBDE's PPB's

PHYSICAL CONSTRUCTION DESCRIPTION Insulated hook-up wire, consisting of 1 conductor, unshielded, and unjacketed.



Part No.	Conductor	Insulation	UL Style	Conductor Resistance Ω/Mft. @20°C	Insulation Resistance MΩ/KFT @20°C	JST Connector
40565-1-S-10000	28 7/36	XL PVC	1571	68	3	ZR
40564-1-S-8000	30 7/38	XL PVC	1571	108	3	SR
40566-1-S-16000	32 7/40	XL PVC	1571	182	3	SSR
40462-1-S-4000	32 7/40	ETFE	10064	224	305	SUR
40085-1-10000	28 7/36	PVC	1061	68	4000	DS/KR

Notes: Some products in stock in white; consult factory for details.
 All data is for reference only and is subject to change.